

# China Oil

## PRODUCT FEATURES

- High performance outdoor oil
- Contains high level of Chinese Tung oil (oil from the Tung Tree nut)
- 41% solids, of which 85% Tung oil
- Suitable for all kinds of untreated wood in outdoor areas
- Low viscosity to penetrate deep into the wood
- High level of protection – contains no fungicide
- Protects the wood from moisture, stains and cracks
- Suitable for both soft and hard woods
- Available in natural and red brown (China Oil teak to retain the natural tone of reddish tropical wood)

## PREPARATION

The wood has to be dry and dust free. If necessary clean with Arboritec Cleaner. Grey wood can be sanded back with a screen. Mouldy wood must be removed and replaced. Due to the high solid content this oil is not suitable as a primer for coating the wood for other products.

## APPLICATION

- Apply China Oil with a brush or a roller until the wood is saturated (125-200g/m<sup>2</sup>). Avoid leaving residues on the surface or oil dropping down to the ground.
- Glossy spots on knots and cracks, and surplus oil must be wiped off before the oil has dried. Due to the oil's special qualities, surplus oil can surface up to 15min after application. Wipe repeatedly with a cloth for a perfect result.
- Let the oil dry for between 24 and 36 hours before use, depending on weather conditions and wood type.
- Repeat the treatment 1 to 2 times during the season.

**Note!** Oil saturated cloths and pads can self-ignite. Store used materials in water or in closed containers.

The trowel and other tools can be cleaned with white spirit before the oil has hardened.

## MAINTENANCE

Clean with Arboritec Cleaner and warm water. Remove algae and organic growth. China Oil slows down the natural greying process of the wood. Grey wood can be removed using a pressure washer or can be sanded with a screen buffer. After removal the wood can be reoiled.

## HEALTH AND ENVIRONMENT

China Oil is not classified under the C.H.I.P. regulations. Use the normal care due when handling chemical products. Ensure good ventilation. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Material Safety Data Sheet.



## TECHNICAL DATA

<b>Contents:</b>	Tungoil and solvents
<b>Usage:</b>	1 litre for 5-8 m <sup>2</sup> , depending on type of wood
<b>Solids content:</b>	41% of which 85% tungoil
<b>Working temp.:</b>	min +5°C (41°F)
<b>Drying time:</b>	24 to 36 hours depending on weather, conditions and type of wood
<b>Storage:</b>	Best before 2 years at max 40°C in unopened container. Once the can is opened the content might start hardening. Store upside down. Keep out of the reach of children. Not sensitive to frost.
<b>Package:</b>	5 litre metal can. Pallet: 600l or 120 cans 1-litre metal can. Pallet: 600l

This Arboritec Product Sheet is intended for advice only. The figures apply to normal conditions, which may vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.

A safety data sheet is available for professional users on request. Keep out of the reach of children.

For technical advice: Contact your distributor or Arboritec Technical Service at +46 303 56330

*The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Arboritec can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product.*

*Rev 13-04-25. This data sheet replaces all previous versions.*