

Hardener

This is an optional hardening component to add to 1 component waterborne lacquers Classic+ and EcoTitan.

Adding a hardener to the lacquer (at a ratio of 1:10) improves the mechanical properties of the 1 component lacquer:

- the lacquer is totally cured within 3 days
- increased wear resistance
- increased chemical resistance
- increased heel mark resistance

INSTRUCTIONS

Prepare the floor according the technical data sheet for the lacquer. Add the hardener to the lacquer at a ratio of 1:10 (one bottle of hardener to one can of lacquer).

Shake or stir the mixture for 1 minute and let it rest for another 10 minutes before application. Do not reseal the can after mixing. Mix only as much as you will need per layer. Once the hardener is added, you cannot store and reuse the lacquer.

Apply the lacquer as instructed on the technical data sheet for that lacquer. Drying times between coats, and time until first use of the floor (24 hours), are not affected by the addition of the hardener.

Bauamtliche Zulassung: DiBT Z-157.10-132 (in 2 component lacquers Genuine und CompoAvenue)

Packaging: 24x450ml

HEALTH AND ENVIRONMENT

Hardener contains aliphatic polyisocyanate.

People with a history of asthma, allergies or chronic/recurring respiratory disease should not be employed in any process in which this product is used. Please consult the safety data sheet for further information.



This Arboritec Product Sheet is intended for advice only. The figures apply to normal conditions, which may vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.

A safety data sheet is available for professional users on request. Keep out of the reach of children.

For technical advice: Contact your distributor or Arboritec Technical Service at +46 303 56330

The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Arboritec can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product.

Rev 13-04-25. This data sheet replaces all previous versions.