


ARBORITEC™

Vibrant

Deep Ambering Ceramic Fortified
WATERBORNE
WOOD FLOOR SEALER



It's the *smallest* things
that make the *biggest*
DIFFERENCE!

Ceramic Silica is one of the most abundant oxide materials in the Earth's crust. It has been known for its hardness since beginning of time and through our incredible **Accelerated NanoTechnology** and specially developed production processes, allows us to create better and more durable, **state of the art sealers**, at the nanoscale, molecule by molecule.

By penetrating the surface, the sealer is chemically and mechanically bonded to the wood, **enhancing the adhesion** and **reducing grain raise**.

**IF IT'S NOT ARBORITEC,
IT'S NOT FINISHED!**



The **Vibrant** advantage:

- **WARMER FEELING** -
Ambers and deepens the natural color of the wood
- **RICHER, DEEPER LOOK** -
May use 2 coats for more intense richer tone
- **EXCEPTIONAL BUILD** -
High solids that seal the floor better than a finish
- **SMOOTHER FLOORS**-
Minimizes grain raise
- **BETTER HEALTH** -
Low VOC for better indoor air quality
- **NATURE FRIENDLY** -
Based on renewable materials

ACCELERATED NANOTECHNOLOGY

Nanotechnology is the art and science of creating materials at the ultra-small nanoscale (down to 1/100 000 the width of a single human hair) to create new and unique products that can work better and last longer. *The nanoscale* is the size of atoms and molecules, the fundamental building blocks of the material world. At the nanoscale, we have been able to affect the properties of materials directly, making our finishes harder and more durable. Simply making things smaller changes their properties. Nanoparticles' small size allows them to get places that conventional particles would not be able to go. This means penetrating deep within the wood, enhancing the *adhesion, strength and scratch resistance*. Since our products are fortified with **Ceramic Silica**, it also solves the problem of white stretch lines. At the end of the day, our Accelerated NanoTechnology is all about doing things differently. **Faster, Stronger, Harder. It's the smallest things that make the biggest difference!**

PRODUCT DESCRIPTION

Arboritec™ Vibrant is a Deep Ambering *Ceramic Fortified* Waterborne Wood Floor Sealer enhanced by Accelerated NanoTechnology. Vibrant sealer ambers and deepens the darker tones and colors of the natural grain of the wood. Vibrant is NMP free and has very low VOC and fast dry time. Vibrant sealer dries hard and delivers a finished result that is easy to abrade and keeps grain raise to a minimum.

DIRECTIONS FOR USE

Sand the floor down to bare wood according to accepted industry standards, such as NWFA. Make sure the surface is dry and free from dust, wax and other contaminants. Vibrant sealer should be at room temperature before using. Temperature of the room, floor and sealer must all be kept the same within the range of 55° F to 86° F. **SHAKE VIGOROUSLY, it doesn't bubble.** For best results, turn jug upside down and shake for approximately 30-45 seconds. Turn the jug on its side and shake for another 30 seconds. Allow the sealer to rest 2-3 minutes before use.

APPLICATION

Arboritec™ Vibrant is suitable for application with a lightweight t-bar applicator, roller or brush. Apply at the rate of 400-500 sq. ft. per gallon. Use extra care in applying the sealer evenly: avoid puddles, lap and stop marks, as this may cause a darker or uneven color. Do not use the same applicator to apply both sealer and finish. Avoid applying in direct sunlight. Make sure Vibrant is completely dry before applying the first coat of Arboritec™ finish. If it is necessary to abrade Vibrant sealer, use a maroon pad or a "used" 150 grit or finer screen. If the first coat of finish is applied within 48 hours, no need to abrade for adhesion. It is always recommended to use Arboritec™ finishes with Arboritec™ sealers for best results on bare wood. It is not recommended to use Vibrant sealer over stain, or with exotic wood species. NOTE: Always test Vibrant sealer on a small area before beginning work to assure compatibility and desired color and results.

ENVIRONMENTAL



Arboritec™ Vibrant is one of the most environmentally conscientious waterborne wood floor sealers available today. Vibrant's unique ambering formula uses modified vegetable oils which are better for the universe and contribute to its key properties. Using renewable resources is one of Arboritec's primary goals in developing better, safer waterborne finishes and sealers, thus, helping you build a better world, one floor at a time. In addition, with a very low VOC (only 75g/L), Vibrant contributes to better, safer and healthier Indoor Air Quality.

TECHNICAL DATA

Special Ingredient	Ceramic Silica	Color	Wet: Light brown, orange Dry: Amber
Recommended Use	Commercial & Residential	Defoaming	Excellent, Virtually no bubbles
Additional Features	NMP Free	Odor	Very light, non-offending
Volatile Organic Compound (VOC)	Maximum of 75 g/L	Toxicity	Non-hazardous
Flow and Leveling	Exceptional	Packaging	3 x 1 gallon
Coverage	400 - 500 sq. ft. per gallon	Storage	Non-flammable, KEEP FROM FREEZING!
Dry Time (68° F, RH 55%)	40-60 min.	Shelf life	12 months in unopened original container
Solids by Volume	Approx. 31-32%	Clean Up	Thoroughly clean all application tools with water, right after using
pH	Approx. 8	Disposal	Dispose in accordance with local regulations
Viscosity (Ford cup 4, 20°C)	19 seconds	Maintenance	Use Arboritec Wood Floor Cleaner™ to keep the floor looking its best
Approx. Weight	8.68 lbs./gallon (1.04 g/cm³)		

PLEASE READ ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEET BEFORE USING.

Arboritec USA, Inc.

6200 S. Syracuse Way, Suite 125 | Greenwood Village, CO 80111 | 877-416-5972
www.arboritec.com © 08/09 Arboritec

**FOR PROFESSIONAL USE ONLY! KEEP FROM FREEZING!
SHAKE VIGOROUSLY - IT DOESN'T BUBBLE!**

