Hard Wax Oil - Version 3 Page 1 of 11



The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued 31.01.2018

1.1. Product identifier

Product name Hard Wax Oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance / preparation

Floor oil.

1.3. Details of the supplier of the safety data sheet

Company name Arboritec AB Postal address Olof Wijksväg 9 Postcode SE-444 65 City Jörlanda Country Sverige Telephone number 0303-563 30 Fax 0303-563 32 Email post@arboritec.com Website http://www.arboritec.com Contact person Jörgen Kaldemark

1.4. Emergency telephone number

Emergency telephone Telephone number: 112

Description: In case of medical emergency call

SECTION 2: Hazards identification

2.1. Classification of substance or mixture

Hard Wax Oil - Version 3 Page 2 of 11

Classification according to
Regulation (EC) No 1272/
2008 [CLP / GHS]

EUH 066

2.2. Label elements

Composition on the label	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics 30 $-$ 40 %, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 20 $-$ 30 %
Hazard statements	EUH 066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P280 Wear protective gloves / protective clothing / eye protection / face protection. P303+P361+P353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. P501 Innehållet/behållaren lämnas till godkänd mottagare av farligt avfall.

2.3. Other hazards

Other hazards

When spray applying see section 8.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	EC No.: 927-285-2 REACH Reg. No.: 01-2119480162-45-0000	Asp. tox 1 EUH 066 H304 Note : Det finns inga inter	30 – 40 %
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%aromatics	CAS No.: 64742-48-9 EC No.: 919-857-5 Index No.: 649-327-00-6 REACH Reg. No.: 01-2119463258-33	Flam. Liq. 3; H226 STOT SE3; H336 Asp. tox 1; H304	20 – 30 %

SECTION 4: First aid measures

4.1. Description of first aid measures

General	Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.
Inhalation	Use with adequate ventilation. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. if breathing is irregular or stopped, use artificial respiration. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice. Get medical advice/attention.
Skin contact	Remove/Take off immediately all contaminated clothing. IF ON SKIN: Wash with plenty of soap and water. Do NOT use solvents or thinners. Wash skin thoroughly with soap and water.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell.

Hard Wax Oil - Version 3 Page 3 of 11

Ingestion	Do NOT induce vomiting. Risk of aspiration or chemical pneumonia. IF SWALLOWED:
	Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable	extinguishing	media

Recommended extinguishing media: alcohol resistant foam, CO2, powders, water spray. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire	and	expl	losion	hazards
	una	CAP	001011	nazarao

Fire will produce dense black smoke. Decomposition products can be hazardous. At high temperatures create: Carbon monoxide (CO), carbon dioxide (CO2), smoke, nitrogen gases (NOx).

5.3. Advice for firefighters

Personal	protective	equip-
ment		

Wear respiratory protection.

Other information

Eliminate all ignition sources if safe to do so. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

See section 7 and 8.

Personal protection measures

In case of inadequate ventilation wear respiratory protection. Wear fire / flame resistant / retardant clothing. Use personal protective equipment as required. Wear cold insulating gloves / face shield / eye protection. Wear protective gloves / protective clothing / eye protection / face protection. Avoid breathing dust / fume / gas / mist / vapours / spray. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

6.2. Environmental precautions

measures

Environmental precautionary Collect spillage. Avoid release to the environment. If the product contaminates lakes, rivers or sewers, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Cleaning method

Keep away from sources of ignition and ventilate the area. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

6.4. Reference to other sections

Hard Wax Oil - Version 3 Page 4 of 11

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling

Vapours may form explosive mixtures with air. Avoid spilling, skin– and eye contact.

Avoid breathing dust / fume / gas / mist / vapours / spray. Avoid breathing dust.

Protective safety measures

Protective safety measures	Smoking, eating and drinking is forbidden in application area. Remove contaminated clothing and protective gear before you get to an area where meals are taken.
Safety measures to prevent fire	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
	In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only non-sparking tools.
Additional information	For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel.

7.2. Conditions for safe storage, including any incompatibilities

Storage	Store in accordance with applicable regulations for good chemical practice. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store in a dry place. Tillse att gällande arbetsmiljölagstiftning följs.
Conditions to avoid	Keep away from heat / sparks / open flames / hot surfaces. — No smoking. Protect from sunlight. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Prevent unauthorized access.

Conditions for safe storage

Storage temperature Value: 5 – 25 Celsius

7.3. Specific end use(s)

Recommendations Do not handle until all safety precautions have been read and understood.

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Substance	Identification	Value	TWA Year
Hydrocarbons, C11-C14,		TWA (8h): 350 mg/m3	TWA Year: 1989
isoalkanes, cyclics, <2% aro-		Source: National Occupa-	
matics		tional Exposure Limit, AFS,	
		for n-paraffin	
		OEL short term value	
		Value: 500 mg/m3	

Hard Wax Oil - Version 3 Page 5 of 11

Source: National Occupational Exposure Limit, AFS ,

for n-paraffin

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,

<2%aromatics

CAS No.: 64742-48-9

TWA (8h): 4 mg/m3

OEL short term value

Value: 12 mg/m3 **Exposure limit letter**Letter description: 15 min

DNEL / PNEC

Substance Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

DNEL Group: Worker

Route of exposure: Long term (repeated) – Dermal – Systemic effect

Value: 208 mg/kg bw/day

Group: Consumer

Route of exposure: Long term (repeated) – Inhalation – Systemic effect

Value: 900 mg/m3

Group: Consumer

Route of exposure: Long term (repeated) – Dermal – Systemic effect

Value: 125 mg/kg bw/day

Group: Worker

Route of exposure: Long term (repeated) – Inhalation – Systemic effect

Value: 871 mg/m3

Group: Consumer

Route of exposure: Long term (repeated) – Oral – Systemic effect

Value: 125 mg/kg bw/day

8.2. Exposure controls

Precautionary measures to prevent exposure

Appropriate engineering controls

Use with adequate ventilation. If possible this should be achieved by local extraction and good exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory equipment.

Eye / face protection

Suitable eye protection

Wear cold insulating gloves / face shield / eye protection.

Hand protection

Hand protection	Wear cold insulating gloves / face shield / eye protection.
Skin- / hand protection, long term contact	For prolonged or repeated contact use gloves made of neoprene (1-4h) or nitrile (>4h).
Suitable materials	Barrier creams may help to protect the skin, but they should however not be used once exposure has occurred.

Skin protection

Hard Wax Oil - Version 3 Page 6 of 11

Skin protection (except hands)

Wear fire / flame resistant / retardant clothing.

Respiratory protection

Respiratory protection Respiratory protection with gas filter (brown A) must be used if air concentration

exceeds acceptable level (OEL).

Mask type When spraying, use half-or full face mask with filter P2 (IIb) to spray.

Exposure controls

Safety measures for consumer use of the chemical Read label before use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. Odour As Solvent. Odour limit Comments: Not applicable. рΗ Status: In delivery state Comments: Not determined. Status: In aqueous solution Comments: Not determined . Melting point / melting range Comments: Not applicable Boiling point / boiling range Comments: Not applicable. Flash point Value: 62 °C Evaporation rate Comments: Not determined. Flammability (solid, gas) Not determined Lower explosion limit with 0,5% unit of measurement Upper explosion limit with 5% units of measurement **Explosion limit** Comments: Not applicable. Vapour pressure Comments: Not determined. Vapour density Comments: Not determined. Specific gravity Value: 0,8 g/ml Method: ASTM6450 Temperature: 23 °C Solubility in water Non-soluble. Partition coefficient: n-oc-Comments: Not applicable. tanol/water Viscosity Value: > 20,5 mm2/s Temperature: 40 °C

Hard Wax Oil - Version 3 Page 7 of 11

Explosive properties Not explosive.

Oxidising properties Not applicable.

9.2. Other information

Physical hazards

Content of VOC Value: 520 g/l

Comments: Initial boiling point less than or equal to 250°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No reactive.

10.2. Chemical stability

Stability Stable under recommended storage and handling conditions (see section 7). Risk of

self-ignition in porous materials such as such as insulation, cloths, etc.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

No dangerous if handled according to Technical Information.

10.4. Conditions to avoid

Conditions to avoid No applicable.

10.5. Incompatible materials

Materials to avoid Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order

to avoid exothermic reaction.

10.6. Hazardous decomposition products

Hazardous decomposition products

When exposed to high temperature may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Substance Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

Acute toxicity Type of toxicity: Acute

Effect tested: LD50
Route of exposure: Oral
Value: > 5000 mg/kg bw
Animal test species: Rat
Test reference: OECD TG 401

Type of toxicity: Acute Effect tested: LD50

Hard Wax Oil - Version 3 Page 8 of 11

Route of exposure: Dermal Value: > 5000 mg/kg bw Animal test species: Kanin Test reference: OECD TG 402

Type of toxicity: Acute Effect tested: LC50

Route of exposure: Inhalation.

Value: > 5000 mg/m3
Animal test species: Rat
Test reference: OECD TG 403

Substance Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity Type of toxicity: Acute Effect tested: LD50

Route of exposure: Dermal Value: > 5000 mg/kg Animal test species: Rabbit

Other information regarding health hazards

Inhalation	Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system.
Skin contact	Prolonged or repeated skin contact may cause irritation, dry skin, cracked skin and possibly eczema.
Eye contact	May cause irritation in eyes.
Ingestion	Ingestion may cause nausea and vomiting. Pneumonia may occur if the product by swallowing or vomiting is drawn into the respiratory tract.
Skin corrosion / irritation, other information	No information available.
Eye damage or irritation other information	If splashed in the eyes, the liquid may cause irritation and reversible damage.
General respiratory or skin sensitisation	Prolonged or repeated contact may defat the skin, resulting in non-allergic contact eczema and absorption through the skin.
Germ cell mutagenicity, human experience	No information available.
Carcinogenicity human experience	No information is available.
Reproductive toxicity	No information available.
STOT-single exposure	No information available.
STOT-repeated exposure	No information available.

SECTION 12: Ecological information

When applying see section 8.

Aspiration hazard, com-

ments

Hard Wax Oil - Version 3 Page 9 of 11

12.1. Toxicity

Substance Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics Acute aquatic, fish **Value:** > 1000 mg/l Test duration: 96h Method: LC50 Substance Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Acute aquatic, fish Value: > 1000 mg/l Test duration: 96h Species: Oncorhynchus mykiss Method: LC50 Substance Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Acute aquatic, algae **Value:** > 1000 mg/l Test duration: 72h Species: Pseudokirchneriella subcapitata Method: IC50 Substance Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics Acute aquatic, Daphnia Value: > 1000 mg/l Test duration: 48h Method: EC50

12.2. Persistence and degradability

Persistence and degradability description	Not determined.
Substance	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics
Biodegradability	Comments: The product is easily biodegradable by microorganisms according to the OECD 301F. Mostly evaporates and floats on water when spill or release. At penetration in deeper soil, the evaporation is considerably more difficult.

12.3. Bioaccumulative potential

Bioaccumulative potential	Not determined.
Substance	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics
Bioconcentration factor (BCF)	Value: 2,16 Comments: Log Pow: 6-7
Substance	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%aromatics
Bioconcentration factor (BCF)	Comments: Log Pow: 5-6,7

12.4. Mobility in soil

Mobility Not determined.

12.5. Results of PBT and vPvB assessment

PBT assessment results Not classified as PBT / vPvB of current EU criteria.	
---	--

Hard Wax Oil - Version 3 Page 10 of 11

12.6. Other adverse effects

Other adverse effects, comments

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Specify the appropriate methods of disposal	Avoid release to the environment. Collect spillage. Wastes and empty containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.
Product classified as haz- ardous waste	Yes
EWC waste code	EWC: 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS, National waste code: 01, National wastegroup: 11

SECTION 14: Transport information

14.1. UN number

Comments

Not dangerous goods.

Transport in accordance with national law and ADR for road, RID for rail, IMDG for sea and ICAO / IATA for air. For complete information on transport, see transport document.

14.2. UN proper shipping name

ADR / RID / ADN	
IMDG	
ICAO / IATA	

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

IMDG Marine pollutant No

INO

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Legislation and regulations The labeling of the product according to EC directives 67/548/EEC, 1999/45/EC, see

Hard Wax Oil - Version 3 Page 11 of 11

section 2.

Classification and labeling of substances according to Regulation (EC) 1272/2008 (CLP) is in section 2.

Classification and labeling of substances under Directive 67/548/EC, 1999/45/EC, see section 3.

Classification and labeling of substances according to Regulation (EC) 1272/2008 (CLP) is in section 3.

Safety data sheet is designed according to EU Commission Regulation No. 1907/2006.

15.2. Chemical safety assessment

Chemical safety assessment No performed

SECTION 16: Other information

List of relevant H-phrases (Section 2 and 3)

EUH 066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/ **EUH 066**

2008 [CLP / GHS]

Version

3

Comments

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.