Satin Oil - Version 7 Page 1 of 9



The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued 31.01.2018

1.1. Product identifier

Product name Satin Oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance / preparation

For maintaining oiled surfaces.

1.3. Details of the supplier of the safety data sheet

Company name Arboritec AB Postal address Olof Wijksväg 9 Postcode SE-444 65 City Jörlanda Country Sverige Telephone number 0303-563 30 Fax 0303-563 32 Email post@arboritec.com Website http://www.arboritec.com Contact person Jörgen Kaldemark

1.4. Emergency telephone number

Emergency telephone Telephone number: 112

Description: In case of medical emergency call

SECTION 2: Hazards identification

2.1. Classification of substance or mixture

Satin Oil - Version 7 Page 2 of 9

Classification according to Regulation (EC) No 1272/ 2008 [CLP / GHS] **EUH 066**

2.2. Label elements

Composition on the label	n-Paraffin C5-20 60 -80 %
Hazard statements	EUH 066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	P280 Wear protective gloves / protective clothing / eye protection / face protection. P303+P361+P353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor. P501 Dispose of contents / container to an approved recipient of hazardous waste.

2.3. Other hazards

Other hazards Whe

When spray applying see section 8.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents	
n-Paraffin C5-20	CAS No.: 64771-72-8	Asp. tox 1; H304	60 -80 %	
	EC No.: 265-233-4	EUH 066		
	REACH Reg. No.:			
	02-2119675247-30-0000			

SECTION 4: First aid measures

4.1. Description of first aid measures

General	Get medical advice/attention. Never give anything by mouth to an unconscious person.
Inhalation	Use with adequate ventilation. Remove victim to fresh air and keep at rest in a position comfortable for breathing. if breathing is irregular or stopped, use artificial respiration. Never give anything by mouth to an unconscious person. Get medical advice/attention.
Skin contact	Remove/Take off immediately all contaminated clothing. IF ON SKIN: Wash with plenty of soap and water. Do NOT use solvents or thinners.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.
Ingestion	Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Risk of aspiration or chemical pneumonia.

4.2. Most important symptoms and effects, both acute and delayed

General symptoms and effects

No specific symptoms exist.

Satin Oil - Version 7 Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

Medical treatment No specific treatment necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended extinguishing media: alcohol resistant foam, CO2, powders, water spray. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards

Fire will produce dense black smoke. Decomposition products can be hazardous. At high temperatures create: Carbon monoxide (CO), carbon dioxide (CO2), smoke, nitrogen gases (NOx).

5.3. Advice for firefighters

Personal protective equipment

Wear respiratory protection.

Other information

Eliminate all ignition sources if safe to do so. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Refer to protective measures listed in sections 7 and 8.

Personal protection measures

In case of inadequate ventilation wear respiratory protection. Wear fire / flame resistant / retardant clothing. Use personal protective equipment as required. Wear cold insulating gloves / face shield / eye protection. Wear protective gloves / protective clothing / eye protection / face protection. Avoid breathing dust / fume / gas / mist / vapours / spray. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

6.2. Environmental precautions

measures

Environmental precautionary Avoid release to the environment. Collect spillage. If the product contaminates lakes, rivers or sewers, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Cleaning method Keep away from sources of ignition and ventilate the area. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous

> earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

Containment Store in a well-ventilated place.

6.4. Reference to other sections

SECTION 7: Handling and storage

Satin Oil - Version 7 Page 4 of 9

7.1. Precautions for safe handling

Handling Vapours may form explosive mixtures with air. Avoid spilling, skin– and eye contact.

Avoid breathing dust / fume / gas / mist / vapours / spray. Avoid breathing dust.

Protective safety measures

Protective safety measures

Remove contaminated clothing and protective gear before you get to an area where meals are taken.

Safety measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Do not eat, drink or smoke when using this product.

Additional information

Never use pressure to empty : container is not a pressure vessel. For personal $% \left(1\right) =\left(1\right) \left(1\right) \left($

protection see Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep only in original container. Store in a well-ventilated place. Keep container tightly

closed. Keep cool. Protect from sunlight. Store in a dry place. Ensure that the safety legislation laws are followed. Store in accordance with applicable regulations for good

chemical practice.

Conditions to avoid Keep away from heat / sparks / open flames / hot surfaces. — No smoking. Protect

from sunlight. Keep away from oxidizing agents, from strongly alkaline and strongly

acid materials. Prevent unauthorized access.

Conditions for safe storage

Storage temperature Value: 5 – 25 Celsius

7.3. Specific end use(s)

Recommendations Do not handle until all safety precautions have been read and understood.

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Substance Identification Value TWA Year

n-Paraffin C5-20 CAS No.: 64771-72-8 TWA (8h) : 350 mg/m3

OEL short term value Value: 500 mg/m3

8.2. Exposure controls

Precautionary measures to prevent exposure

Satin Oil - Version 7 Page 5 of 9

Appropriate engineering controls	Use with adequate ventilation. If possible this should be achieved by local extraction
CONTROLS	and good exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory equipment.

Eye / face protection

Suitable eye protection Wear cold insulating gloves / face shield / eye protection.

Hand protection

Hand protection	Wear cold insulating gloves / face shield / eye protection.
Skin- / hand protection, long term contact	For prolonged or repeated contact use gloves made of neoprene (1-4h) or nitrile (>4h).
Suitable materials	Barrier creams may help to protect the skin, but they should however not be used once exposure has occurred.

Skin protection

Skin protection (except	Wear fire / flame resistant / retardant clothing.
hands)	

Respiratory protection

Respiratory protection	Respiratory protection with gas filter (brown A) must be used if air concentration exceeds acceptable level (OEL).
Mask type	When spraying, use half-or full face mask with filter P2 (IIb) to spray.

Exposure controls

Safety measures for con-	Read label before use.
sumer use of the chemical	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	As solvent.
Odour limit	Comments: Not applicable.
рН	Status: In delivery state Comments: Not determined.
	Status: In aqueous solution Comments: Not determined .
Melting point / melting range	Comments: Not determined.
Boiling point / boiling range	Comments: Not determined.
Flash point	Value: 65 °C
Evaporation rate	Comments: Not determined.
Flammability (solid, gas)	flammable class 3

Satin Oil - Version 7 Page 6 of 9

Lower explosion limit with Value: 0.6 % unit of measurement Upper explosion limit with Value: 6,5 % units of measurement Vapour pressure Comments: Not determined. Vapour density Comments: Not determined. Specific gravity Value: 0,78 g/ml Method: ASTM 6450 Temperature: 20 °C Solubility in water Non-soluble. Partition coefficient: n-oc-Comments: Not applicable. tanol/water Viscosity Value: > 20,5 mm2/s Temperature: 40 °C Explosive properties Not explosive.

9.2. Other information

Physical hazards

Content of VOC Value: 616 g/l

Comments: Initial boiling point less than or equal to 250°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No reactive.

10.2. Chemical stability

Stability

Stable under recommended storage and handling conditions (see section 7).

Risk of self-ignition in porous materials such as such as insulation, cloths, etc.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

No dangerous if handled according to Technical Information.

10.4. Conditions to avoid

Conditions to avoid No applicable.

10.5. Incompatible materials

Materials to avoid Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reaction.

10.6. Hazardous decomposition products

Hazardous decomposition	When exposed to high temperature may produce hazardous decomposition products
products	

Satin Oil - Version 7 Page 7 of 9

such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other information regarding health hazards

Inhalation	Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system.
Skin contact	Prolonged or repeated skin contact may cause irritation, dry skin, cracked skin and possibly eczema.
Eye contact	May cause irritation in eyes.
Ingestion	Ingestion may cause nausea and vomiting. Pneumonia may occur if the product by swallowing or vomiting is drawn into the respiratory tract.
Skin corrosion / irritation, other information	No information available.
Eye damage or irritation other information	If splashed in the eyes, the liquid may cause irritation and reversible damage.
General respiratory or skin sensitisation	Prolonged or repeated contact may defat the skin, resulting in non-allergic contact eczema and absorption through the skin.
Eye contact	No information available.
Germ cell mutagenicity, human experience	No information available.
Carcinogenicity human experience	No information is available.
Reproductive toxicity	No information available.
STOT-single exposure	No information available.
STOT-repeated exposure	No information available.
Aspiration hazard, human experience	When applying see section 8.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic, comments Low toxicity to aquatic organisms.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential Not determined.

12.4. Mobility in soil

Mobility	Not determined.

Satin Oil - Version 7 Page 8 of 9

12.5. Results of PBT and vPvB assessment

PBT assessment results

Not classified as PBT / vPvB of current EU criteria.

12.6. Other adverse effects

Other adverse effects, comments

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Specify the appropriate methods of disposal

Collect spillage. Avoid release to the environment. Wastes and empty containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Product classified as hazardous waste

Yes

EWC waste code

EWC: 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS, National waste code: 01, National wastegroup: 11

wastegroup. 11

SECTION 14: Transport information

14.1. UN number

Comments

Not dangerous goods.

Transport in accordance with national law and ADR for road, RID for rail, IMDG for sea and ICAO / IATA for air. For complete information on transport, see transport document.

14.2. UN proper shipping name

ADR / RID / ADN	
IMDG	
ICAO / IATA	

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

IMDG Marine pollutant No

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Satin Oil - Version 7 Page 9 of 9

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Legislation and regulations Classification and labeling of substances under Directive 67/548/EC, 1999/45/EC, see section 3.

> Classification and labeling of substances according to Regulation (EC) 1272/2008 (CLP) is in section 3.

The labeling of the product according to EC directives 67/548/EEC, 1999/45/EC, see section 2.

Classification and labeling of substances according to Regulation (EC) 1272/2008 (CLP) is in section 2.

Safety data sheet is designed according to EU Commission Regulation No. 1907/2006.

15.2. Chemical safety assessment

Chemical safety assessment No performed

SECTION 16: Other information

List of relevant H-phrases (Section 2 and 3)

EUH 066 Repeated exposure may cause skin dryness or cracking. H304 May be fatal if swallowed and enters airways.

Classification according to Regulation (EC) No 1272/ 2008 [CLP / GHS]

EUH 066

Version

Comments

7

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.