



# Miracle Oil

2-Component Commercial  
Wood Floor Oil

 **MADE IN SWEDEN**

## 100% SOLID

Arboritec Miracle Oil™ preserves and protects the natural richness and color of wood floors with a rich patina look. Miracle Oil™ is easy to maintain and repair without re-sanding. Miracle Oil™ is produced with all natural, renewable and sustainable resources and contains no harmful, toxic chemicals.

**Safe for you, and safe for the environment.**



**PLEASE READ ALL INSTRUCTIONS AND SAFETY DATA SHEET BEFORE USING.**

# Miracle Oil



## PRODUCT DESCRIPTION

Arboritec Miracle Oil™ is a 2 component wood floor sealing and finishing oil which provides a very durable protective finish and gives the floor a very rich, natural patina surface. Miracle Oil is quick drying, easy to clean and can be recoated and or repaired without sanding. Miracle Oil is designed to be used as a one coat system for a residential application or a two coat system for commercial high traffic floors. All Miracle Oil base colors can be mixed to create a custom color to your liking.

## DIRECTIONS FOR USE

Sand the floor according to accepted industry standards, such as the NFWA™ recommendations. The final cut should be 100 grit. Make sure the surface is dry and free from dust, wax, grease and other contamination. Temperature of the room, floor and Miracle Oil must all be kept the same within the range of 65°F to 80°F. Relative humidity should be between 40% and 60%. Stir components A & B thoroughly and evenly – DO NOT THIN.

## APPLICATION

Apply Arboritec Miracle Oil directly to the floor. Pour a puddle approximately 5" in diameter. The puddle should be poured 18-24" away from any walls. Place red polishing pad directly on top of the puddle and buff until the floor does not accept any more oil. Add Miracle Oil as needed to ensure an even coverage for best results. Repeat process when adding a second coat. A newly oiled floor will be fully cured, and ready for regular, normal use in 12 hours.

Trowel method for applying Miracle Oil: Using a stainless steel trowel, apply evenly and thinly to the surface at a rate of 325-550 sq. ft. per liter.

CAUTION! A danger of self-ignition (spontaneous combustion) exists in contact with organic materials (cotton cloths, sawdust, rags etc.). Rags and other organic materials soaked in oil have must be placed into tightly sealed container with water to prevent the risk of fire.

## TECHNICAL DATA



<b>Binding Agent</b>	Based on Linseed Oil
<b>Recommended Use</b>	Commercial & Residential
<b>Additional Features</b>	Solvent Free
<b>Coverage</b>	325 - 550 sq. ft. per liter
<b>Dry Time (68° F, RH 55%)</b>	15-30 min after 1st application 2.5 hours after 2nd application
<b>Full Cure</b>	12 hours
<b>Solids by Volume</b>	Approx. 100%
<b>Pot Life</b>	12 hours after mixing
<b>Application Temperature Between</b>	65°F to 80°F Do not expose to temp over 100°F

<b>Color</b>	Natural, White, X-White, Gray, Black, Brown, Red-Brown, Red-Mahogany
<b>Thinner</b>	Linseed oil
<b>Odor</b>	Very light, non-offending.
<b>Toxicity</b>	Non-hazardous
<b>Packaging</b>	1 liter steel can in solid paper tube, including component B hardener.
<b>Storage</b>	Non-flammable, KEEP FROM FREEZING!
<b>Shelf life</b>	12 months in unopened original container.
<b>Clean Up</b>	Thoroughly clean all application tools with mineral spirits, right after using.
<b>Disposal</b>	Dispose in accordance with local regulations.
<b>Maintenance</b>	For normal maintenance, use Arboritec™ Wood Floor Cleaner. To keep the floor looking its best. To repair worn or damaged areas, use Arboritec™ Miracle Maintenance Oil.

There are no express or implied warranties, including warranties of merchantability and/or fitness for a particular purpose. Buyers' remedies are limited to replacement or refund of the purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability of product for intended use.